

WORKING BEYOND LIMITS



POWERBULLY 9D



Payload
7,500 kg | 16,500 lbs



Ground pressure
0.22 kg/cm² | 3.12 psi



Max. speed
14.5 km/h | 9.0 mph



Tare weight
12,450 kg | 27,400 lbs



Fording depth
1,200 mm | 47.2"



Gradeability
60 % uphill & downhill, 40 % sidehill



Capacity heaped (ISO 6483)
5.2 m³ | 6.8 yd³

ENGINE & POWER

Type	Cummins B6.7 Turbo Diesel
No. of cylinders	6
Displacement	6.7 l / 6,700 ccm
Power Output @ 2,000 rpm	173 kW / 235 hp
Max. torque @ 1,500 rpm	949 Nm 700 ft lb
Emission standard	EU Stage V Tier 4f
Drive train:	Hydrostatic Bosch Rexroth drive train

TANK VOLUMES

Diesel	250 l 66 gal
AdBlue	38 l 10 gal
Hydraulic oil	52 l 14 gal

CHASSIS

Track type	Endless rubber track
Track width	700 mm 27.6"
Frame type	C-shaped profile
Frame width	864 mm 34"
Wheels	8 steel wheels
Walking beam	
Automatic track tensioning	
Ground pressure (empty)	0.22 kg/cm ² 3.12 psi
Ground pressure (loaded)	0.35 kg/cm ² 4.97 psi

CABIN


Wide cab	10.4" Touch Display	Sun blind
Suspended cab	Armrest with controls	Air-conditioned cup holder
ROPS / FOPS (Level I and II) certified	Heating, temperature and fan control	Limp home mode
Single-hand joystick operation	Air conditioning	
Adjustable operator's seat	12V power outlet	Illumination
2 axis inclination sensor	2 USB charging ports (type A and C)	6 LED working lights front and rear
Rear view camera	Mobile phone tray	

OPTIONS

Safety	Comfort	Cold start	Others
Premium LED working lights	Air suspended comfort seat	Heated fuel filter	Telematics
Beacon light	Adjustable steering wheel	Feeder pressure reduction	Reversible fan
Auxiliary lights (High and low beam, rear light, indicators)	Heated, electrically adjustable mirrors	Engine block heater 230V/110V	Frame extension (front) 500 or 700 mm 19.7"-27.6"
360° camera (on request)	Radio with Bluetooth and a hands-free kit	Electrical Hydraulic Oil Heating 230V/110V	Narrow cab
Foldable front brush guard		Auxiliary heating	Trailer coupling
FOPS level II protective grid			Air-intake in steel-version
Hydraulic winch (Tractive force: 9 t 19,000 lbs)			Cyclonic pre-separator for air intake

POWERBULLY 9D

DIMENSIONS



Optional: Frame extension front 500 mm | 19.7" or 700 mm | 27.6"

A 2,590 mm | 102"

B 2,450 mm | 96"

C 390 mm | 15.4"

D 700 mm | 27.6"

E 1,412 mm | 55.6"

F 6,091 mm | 240"

G 5,500 mm | 217"

H 4,672 mm | 184"

I 1,689 mm | 66.5"

J 2,857 mm | 112"

K 1,200 mm | 47.2"


L 536 mm | 21"

M 4,912 mm | 193"

a1 68° **a2** 16° **a3** 22°

Optional: Narrow cab **E** 982 mm | 39"

HARDOX DUMP BOX / AUTOMATIC LOWERING



Optional: Dump box with mechanical tailgate

Capacity heaped (ISO 6483) 5.2 m³* | 6.8 yd³*

Capacity leveled 3.2 m³* | 4.2 yd³*


Length 3,400 mm | 134"

Width 2,444 mm | 96"

Side wall height 512 mm | 20.1"

* Applies for dump box with mechanical tailgate

OFF-ROAD ABILITIES



A Sidehill 40% | 22°

B Uphill | Downhill 60% | 31°

C Approach angle 45°

D Departure angle 45°

E Fording depth 1,200 mm | 47.2"

Approach and departure angles deviating with frame extensions



Learn more about PowerBully:
powerbully.com
sales@powerbully.com

PowerBully
TRACK CARRIER